JC Pacific Trading Co.

LIGHT/MEDIUM DUTY POLYURETHANE ON POLYPROPYLENE CASTER

With Plastic Thread Guards

APPLICATIONS:

Polyurethane tread, 90+ shore (A) durometer, chemically bonded to Polypropylene core, non-marking floor protection, resistant to oil, grease, water and most solvents, available in a variety of colors.

SPECIFICATIONS:

SWIVEL: Two rows of ball bearings

in hardened raceways.

FORK: 1/8" formed steel plate

AXLE: 1/4" diameter bolt and nut for


small plate;


3/8" diameter bolt & nut for


large plate.

FINISH: Chrome or Zinc Plated.









Part#	Description	Packing (PC)	Overall Height (inches)	Weight (LB)	Capacity (LB)
S5×1.25PP	5"×1 1/4"Small Plate Polyurethane on Polypropylene Swivel	500	6"	2 3/4	350
R5×1.25PP	5"×1 1/4"Small Plate Polyurethane on Polypropylene Rigid	500	6"	2 1/2	350
S4×1.25PP	4"×1 1/4"Small Plate Polyurethane on Polypropylene Swivel	800	5"	2	300
R4×1.25PP	4"×1 1/4"Small Plate Polyurethane on Polypropylene Rigid	800	5"	1 1/4	300
LS5×1.25PP	5"×1 1/4"Large Plate Polyurethane on Polypropylene Swivel	500	6"	3	350
LR5×1.25PP	5"×1 1/4"Large Plate Polyurethane on Polypropylene Rigid	500	6"	2 1/2	350
LS4×1.25PP	4"×1 1/4"Large Plate Polyurethane on Polypropylene Swivel	800	5"	2 1/4	300
LR4×1.25PP	4"×1 1/4"Large Plate Polyurethane on Polypropylene Rigid	800	5"	1 1/2	300